


CLOCK OSCILLATORS TTL COMPATIBLE (Rohs Compliant / Lead Free)
Oscillators Full Size (APO-FTL Series) 5V




- SPECIFICATIONS

FREQUENCY RANGE		0.5MHz TO 23.999MHz	24MHz TO 69.999MHz	70MHz TO 150MHz
FREQUENCY STABILITY (ALL INCLUSIVE*)		±20PPM, ±25PPM, ±50PPM, ±100PPM		
TEMPERATURE RANGE	OPERATING	0°C TO +70°C STANDARD		
		-40°C TO +85°C EXTENDED		
	STORAGE	-55°C TO +125°C		
AGING (FIRST YEAR)		±5PPM		
INPUT	VOLTAGE	+5VDC ±10%		
	CURRENT (MAX.)	15mA	30mA	60mA
OUTPUT	LOAD TTL	1 ~ 10TTL		
	SYMMETRY	NORMAL: 40% TO 60%		
		TIGHT: 45% TO 55%		
	VOLTAGE	V_{OH}	2.4V min	
V_{OL}		0.4V max		
	RISE/FALL TIME	5nS Max (Tr: 0.4V~2.4V, Tf: 2.4V~0.4V)		
START-UP TIME		10mS max		




*Include: 25°C tolerance, operating temperature range, input voltage change, aging 1st year, load change, shock and vibration

- OUTLINE DIMENSIONS



PIN	CONNECTION
#1	NC
#7	Ground
#8	Output
#14	VDD

- SOLDER REFLOW PROFILE



ORDERING CODE SYSTEM (VERSION 1.1 UPDATED MAY 2008)						EXAMPLE:
SERIES	STABILITY	FREQUENCY	INPUT VOLTAGE	TEMPERATURE RANGE	OPTIONAL / BLANK	APO-FTLJ-25-5XT
APO-FTL	D: ±20PPM E: ±25PPM J: ±50PPM P: ±100PPM	IN MHZ	5	X: EXTENDED TEMPERATURE (-40 TO +85 °C)	T – TIGHT SYMMETRY OTHERS – SPECIAL BLANK - STANDARD	

NON STANDARD FREQUENCIES AND SPECIFICATIONS ARE AVAILABLE ON REQUEST

ActPro Ltd. (APX-Crystal) PROREP EDGE Meditronics PTE Ltd.	HONG KONG FRANCE SINGAPORE	Email: sales@apx-crystal.com Email: sales@prorep.fr Email: sales@edgemeditronics.com.sg	Internet: www.apx-crystal.com Internet: www.prorep.fr Internet: www.edgemeditronics.com.sg	Tel: 852-3625 2368 Tel: 33-1-4812 1736 Tel: 65-6455 0521	Fax: 852-2633 8503 Fax: 33-1-4812 1739 Fax: 65-6455 0857
--	----------------------------------	---	--	--	--

Specifications are subject to change without notice